

# ENTRY POINT SCREENING DEVICES PRODUCT GUIDE

## High-Volume Screening and Access Control Solutions

Customizable features and functions for the optimal screening of employees, contractors, and visitors. Designed to stand alone or be sequenced with existing access control measures.



### Kiosk

A well-designed and technically sound device providing facial recognition technology with 99.9% accuracy and an identification speed of 300 ms. Intelligent Temperature Measurements yield highly-accurate, and rapid readings.



### Wall Mount

Completely automated and noninvasive with easy to understand verbal commands.

**Phoebus Basic:** on-screen display allows playback of video presentations.

**Phoebus Advanced:** offers high-speed facial recognition combined with a NFC reader for identification of employees.



### Gated Entry

Reduce on-site accidents resulting from alcohol usage with alcohol-specific, fuel cell sensor technology. Ideal for safety-sensitive industries such as Manufacturing and Construction.

#### KEY PRODUCT FEATURES

- Facial Recognition
- Live Detection
- Fingerprint Scanner
- Alcohol Testing
- High-Speed Detection
- Temperature Detection
- Real-Time Data Upload
- NFC Card Reader
- Wall Mount Design

SPECIFICATION	KIOSK	WALL MOUNT	GATED ENTRY
<b>Size</b>	128 x 18 x 236mm	200 x 220 x 88mm	140 x 195 x 400mm
<b>Weight</b>	2.8 lbs	2.7 lbs	6.17 lbs
<b>Temperature Accuracy</b>	±0.54°F	±0.54°F	±0.54°F
<b>BrAC Accuracy</b>	N/A	0 - 0.10% BrAC ±5% 0.10 - 0.15% BrAC ±8% >0.15%: ±10%	0 - 0.10% BrAC ±5% 0.10 - 0.15% BrAC ±8% >0.15%: ±10%
<b>Facial Recognition Time</b>	< 1 second	< 1 second	< 1 second
<b>Alcohol Measurement Response Time</b>	N/A	5 seconds	5 seconds
<b>Memory (in device)</b>	5,000 test records 20,000 registered faces	20,000 test records 10,000 registered faces	20,000 test records 20,000 registered faces
<b>Network</b>	WiFi, 4G (optional), Ethernet	WiFi, 4G (optional), Ethernet	WiFi, 4G (optional), Ethernet

LEARN MORE ABOUT PAS SENSORS  
VISIT [WWW.PASINTL.COM](http://WWW.PASINTL.COM)

